



Note: Non standard sizes on request

PLEASE NOTE INBUILT TOLERANCE

If setting out your studwork before delivery of your frame please note there is approximately an 8mm tolerance built into the height of these pocket door systems which you will need to take into account. Packers may be required to accommodate for this gap if you are unable to adjust the studwork above the system.

Note: Frame should be installed at finished floor level.

FRAMES FOR SINGLE DOORS			DOOR PANELS UK	
MAX. PASSAGE SIZE PW x PH	OVERALL DIMENSION W x H	FINISHED WALL FW	DW	DH
600 x 2030	1307 x 2120	150	626	2040
700 x 2030	1507 x 2120	150	726	2040
800 x 2030	1707 x 2120	150	826	2040
900 x 2030	1907 x 2120	150	926	2040
1000 x 2030	2107 x 2120	150	1026	2040
585 x 1971	1292 x 2061	150	2ft. 0in. x 6ft. 6in. (610 x 1981 mm)	
661 x 1971	1468 x 2061	150	2ft. 3in. x 6ft. 6in. (686 x 1981 mm)	
737 x 1971	1644 x 2061	150	2ft. 6in. x 6ft. 6in. (762 x 1981 mm)	
813 x 1971	1720 x 2061	150	2ft. 9in. x 6ft. 6in. (838 x 1981 mm)	
900 x 1971	1907 x 2061	150	3ft. 0in. x 6ft. 6in. (914 x 1981 mm)	
675 x 1971	1482 x 2061	150	2ft. 4in. x 6ft. 6in. (711 x 1981 mm)	
775 x 2020	1682 x 2110	150	2ft. 8in. x 6ft. 8in. (813 x 2032 mm)	
850 x 2020	1857 x 2110	150	2ft. 10in. x 6ft. 8in. (864 x 2032 mm)	

Dimensions are given in mm



NOTES

- ▶ Non standard sizes available up to PW 1300 x PH 2600 mm.
- ▶ Suitable for 35 to 44 mm thick doors.
- ▶ Standard single units have the possibility to use sockets on both sides of the pocket.
- ▶ Maximum socket depth 44 mm.
- ▶ Doors, plasterboard and final architrave not supplied.
- ▶ When fitting flush pull handles we recommend the stop be regulated so the door protrudes from the pocket to avoid risk to fingers.
- ▶ Should the door be set to enter the pocket completely we do not accept any liability.
- ▶ The framework is not designed to take heavy loads such as radiators etc.
- ▶ Install at finished floor level.
- ▶ Max door weight 100 kg (150 kg on request).



ACCESSORIES

- ▶ **Door Furniture**
Flush pulls and bathroom locks
- ▶ **ECLISSE BIAS®**
Soft close up to 40 kg with anti-slam
- ▶ **ECLISSE BIAS® DS**
Bi-directional soft close up to 40 kg with anti-slam
- ▶ **Soft Close**
Slide the door towards the close position, the soft close takes over
- ▶ **Self Closing Mechanism**
Open the door and it closes by itself!
- ▶ **E-MOTION**
Linear motor open/close