


CLASSIC LUCE DOUBLE - wiring ready

DOUBLE POCKET DOORS SYSTEM

Double Sliding Pocket Door system
Wiring/Socket Ready



N.B.: Non standard sizes on request

FRAMES FOR DOUBLE DOORS			DOOR PANEL UK	
MAX. PASSAGE SIZE	OVERALL DIMENSION	FINISHED WALL	DW	DH
PW x PH	W x H	FW		
1200 x 2030	2520 x 2115	150	626	2040
1400 x 2030	2920 x 2115	150	726	2040
1600 x 2030	3320 x 2115	150	826	2040
1800 x 2030	3720 x 2115	150	926	2040
2000 x 2030	4120 x 2115	150	1026	2040
1170 x 1971	2490 x 2056	150	2ft. 0in. x 6ft. 6in. (610 x 1981 mm)	
1322 x 1971	2842 x 2056	150	2ft. 3in. x 6ft. 6in. (686 x 1981 mm)	
1474 x 1971	3194 x 2056	150	2ft. 6in. x 6ft. 6in. (762 x 1981 mm)	
1626 x 1971	3346 x 2056	150	2ft. 9in. x 6ft. 6in. (838 x 1981 mm)	
1800 x 1971	3720 x 2056	150	3ft. 0in. x 6ft. 6in. (914 x 1981 mm)	

Dimensions are given in mm



NOTES

- ▶ Available in non standard sizes up to 2600 x 2600 mm passage size.
- ▶ Standard double units have the possibility to use sockets on both sides of one pocket, both pockets on request.
- ▶ Maximum socket depth 44 mm.
- ▶ Suitable for 35 to 44 mm thick doors.
- ▶ Max door weight 100 kg (150 kg on request).
- ▶ When fitting flush pull handles we recommend the stop be regulated so the door protrudes from the pocket to avoid risk to fingers.
- ▶ Should the door be adjusted to enter the pocket completely we do not accept any liability.
- ▶ The framework is not designed to take heavy loads such as radiators e.t.c..
- ▶ Doors, plasterboard and final architrave not supplied.
- ▶ Install at finished floor level.



ACCESSORIES

- ▶ **Door Furniture**
Flush Pulls
- ▶ **ECLISSE BIAS®**
Safety Soft Close anti-slam device with 40 kg soft closing
- ▶ **ECLISSE BIAS® DS**
Bi-directional Safety soft close up to 40 kg with anti-slam
- ▶ **Soft Close**
Slide the door towards the close position and the soft close takes over
- ▶ **Double door Co-ordination**
Doors open and close simultaneously